

MATERIAL SAFETY DATA SHEET

Toluene/Acetone 50:50 v/v Solution

SECTION 1 . Product and Company Identification

Product Name and Synonym: Toluene/Acetone 50:50 v/v Solution

Product Code: 0122

Material Uses:

Manufacturer: Science Stuff
1104 Newport Ave

Austin, TX 78753

(512) 837-6020

Entry Date : 5/23/2013

Print Date: 5/23/2013

24 Hour Emergency Assistance : Chemtrec 800-424-9300
Canutec 613-996-6666

Health:	2
Flammability:	3
Reactivity:	0

Hazard Rating:
Least Slight Moderate High Extreme
0 1 2 3 4
NA=Not Applicable NE=Not Established

SECTION 2 HAZARD IDENTIFICATION

Keep away from heat and ignition sources. May be harmful if swallowed. Avoid breathing vapor or dust. Use with adequate ventilation. Avoid contact with eyes, skin, and clothes. Wash thoroughly after handling. Keep container closed.

SECTION 3 MIXTURE COMPONENTS

SARA 313	Component	CAS Number	Percent Comp.	Dimension	Exposure Limits
<input type="checkbox"/>	Acetone	CAS# 67-64-1	50%	V/V	OSHA TWA 1000 ppm (2400 mg/mf)
<input checked="" type="checkbox"/>	Toluene	CAS# 108-88-3	50%	V/V	OSHA TWA 200 ppm

SECTION 4 FIRST AID MEASURES

Keep away from heat and ignition sources. May be harmful if swallowed. Avoid breathing vapor or dust. Use with adequate ventilation. Avoid contact with eyes, skin, and clothes. Wash thoroughly after handling. Keep container closed.

FIRST AID: SKIN: Remove contaminated clothing. Wash exposed area with soap and water. if irritation persists, seek medical attention.

EYES: Wash eyes with plenty of water for at least 15 minutes, lifting lids occasionally. Seek Medical Aid. INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen

INGESTION: If swallowed, induce vomiting immediately after giving two glasses of water. Never give anything by mouth to an unconscious person.

SECTION 5 FIRE FIGHTING MEASURES

Fire Extinguisher Type: Carbon Dioxide, dry chemical powder or appropriate foam

Fire / Explosion Hazards: Vapor may travel considerable distance to source of ignition and flash back.

Toluene/Acetone 50:50 v/v Solution

Fire Fighting Procedure: Use water spray to cool fire exposed containers.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Eliminate ignition sources. Absorb spill with inert material, then place in a chemical waste container. Dispose of in a manner consistent with federal, local law.

SECTION 7 HANDLING AND STORAGE

Store in a cool, dry, well-ventilated place away from incompatible materials. Wash thoroughly after handling.

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory Protection: NIOSH/MSHA-approved respirator

Ventilation

Local Exhaust

Mechanical

Protective Gloves: Wear appropriate gloves to prevent skin exposure

Eye Protection: Splash Goggles

Other Protective Equipment: Wear appropriate clothing to prevent skin exposure

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Melting Point:	Information not available	Percent Volatile by Volume:	>99
Boiling Point:	Information not available	Evaporation Rate	Information not available
Vapor Pressure:	Information not available	Evaporation Standard	
Vapor Density:	Information not available	Auto Ignition Temp	Information not available
Solubility in Water:	Soluble	Lower Flamm. Limit in Air	Information not available
Appearance /Odors:	Clear, colorless liquid, strong aromatic odor	Upper Flamm. Limit in Air	Information not available
Flash Point:	Information not available		
Specific Gravity:	~0.9		

SECTION 10 STABILITY AND REACTIVITY INFORMATION

Stability: Stable

Conditions to Avoid: Avoid contact with heat, sparks, flames, or other sources of ignition.

Toluene/Acetone 50:50 v/v Solution

Materials to Avoid: Strong oxidizers, metals, strong bases, amines
Hazardous Decomposition Products: Toxic oxides of Carbon
Hazardous polymerization: Will Not Occur
Conditions to Avoid: None known

SECTION 11 Toxicological Information

SECTION 12 Ecological Information

SECTION 13 Disposal Considerations

SECTION 14 Transport Information

DOT Classification: Flammable liquids, n.o.s. (Acetone and Toluene), 3, UN1993, PG II

DOT Regulations may change from time to time. Please consult the most recent D.O.T. regulations.

SECTION 15 Regulatory Information

SECTION 16 Additional Information

DANGER!! This material can cause brain and central nervous system damage with repeated exposure. Conditions aggravated/target organs: Toxic! Persons with preexisting skin, eye and respiratory conditions will be more susceptible. Acute: Skin, eye, respiratory tract and digestive tract irritation, headache, dizziness, central nervous system effects, kidney and liver damage, cardiac arrest. Chronic: Dermatitis, defatting of skin, eye damage.

Flammability

Health

Reactivity

Revisions

NFPA

0.1

The information herein is believed to be accurate and is offered in good faith for the user's consideration and investigation. No warranty either expressed or implied is made for the completeness or accuracy of the information whether originating from the above mentioned company or not. Users of this material should satisfy themselves by independent investigation of current scientific and medical knowledge that the material can be used safely.