

MATERIAL SAFETY DATA SHEET

Lithium Standard 1,000 ppm

SECTION 1 . Product and Company Identification

Product Name and Synonym: Lithium Standard 1,000 ppm
Product Code: 5350
Material Uses:
Manufacturer: Science Stuff
1104 Newport Ave
Austin, TX 78753
(512) 837-6020
Entry Date : 6/11/2013
Print Date: 6/11/2013
24 Hour Emergency Assistance : Chemtrec 800-424-9300
Canutec 613-996-6666

Health:	3
Flammability:	0
Reactivity:	0

Hazard Rating:
Least Slight Moderate High Extreme
0 1 2 3 4

NA=Not Applicable NE=Not Established

SECTION 2 HAZARD IDENTIFICATION

Causes severe irritation and burns. Harmful if swallowed. Avoid breathing vapor or dust. Use with adequate ventilation. Avoid contact with eyes, skin, and clothes. Wash thoroughly after handling. Keep container closed.

SECTION 3 MIXTURE COMPONENTS

SARA 313	Component	CAS Number	Percent Comp.	Dimension	Exposure Limits
<input type="checkbox"/>	Lithium Nitrate	CAS# 7790-69-4	<1%	W/V	None established
<input checked="" type="checkbox"/>	Nitric Acid	CAS# 7697-37-2	3 - 3.5%	W/V	OSHA TWA 2 ppm (5mg/m ³), STEL 4 ppm (10mg/m ³)
<input type="checkbox"/>	Water, Deionized ASTM Type II	CAS# 7732-18-5	Balance	V/V	None Established

SECTION 4 FIRST AID MEASURES

Causes severe irritation and burns. Harmful if swallowed. Avoid breathing vapor or dust. Use with adequate ventilation. Avoid contact with eyes, skin, and clothes. Wash thoroughly after handling. Keep container closed.

FIRST AID: CALL A PHYSICIAN. SKIN: Remove contaminated clothing. Wash exposed area with soap and water.

EYES: Wash eyes with plenty of water for at least 15 minutes, lifting lids occasionally. Seek Medical Aid. INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen

INGESTION: Give several glasses of milk or water. Vomiting may occur spontaneously, but DO NOT INDUCE! Never give anything by mouth to an unconscious person.

SECTION 5 FIRE FIGHTING MEASURES

Fire Extinguisher Type: Any means suitable for extinguishing surrounding fire

Lithium Standard 1,000 ppm

Fire / Explosion Hazards: Thermal decomposition produces highly toxic fumes.
Fire Fighting Procedure: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and clothing.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Absorb spill with inert material, then place in a chemical waste container. Neutralize with a weak base.

SECTION 7 HANDLING AND STORAGE

Store in a cool, dry, well-ventilated place away from incompatible materials. Wash thoroughly after handling.

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory Protection: None required
Ventilation
Local Exhaust
Mechanical
Protective Gloves: NIOSH Approved Gloves
Eye Protection: Splash Goggles
Other Protective Equipment: Wear appropriate clothing to prevent skin exposure

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Melting Point:	~0°C	Percent Volatile by Volume:	>99%
Boiling Point:	~100°C	Evaporation Rate	0.36
Vapor Pressure:	Information not available	Evaporation Standard	Butylacetate =1
Vapor Density:	Information not available	Auto Ignition Temp	Not applicable
Solubility in Water:	Soluble	Lower Flamm. Limit in Air	Not applicable
Appearance /Odors:	Clear odorless liquid	Upper Flamm. Limit in Air	Not applicable
Flash Point:	Not applicable		
Specific Gravity:	1.017		

SECTION 10 STABILITY AND REACTIVITY INFORMATION

Stability: Stable
Conditions to Avoid: Avoid freezing and contact with incompatible materials.
Materials to Avoid:
Hazardous Decomposition Products: Hydrogen, oxides of nitrogen
Hazardous polymerization: Will Not Occur
Conditions to Avoid: None known

Lithium Standard 1,000 ppm

SECTION 11 Toxicological Information

SECTION 12 Ecological Information

SECTION 13 Disposal Considerations

SECTION 14 Transport Information

DOT Classification: UN3264, Corrosive Liquid, Acidic, Inorganic
n.o.s. (Nitric Acid), 8, PG III

DOT Regulations may change from time to time. Please consult the most recent D.O.T. regulations.

SECTION 15 Regulatory Information

SECTION 16 Additional Information

Conditions aggravated/target organs: Corrosive! Oxidizer! Hazardous in case of eye contact (corrosive) May cause burns. Hazardous in case of skin contact (corrosive). Skin contact may product burns. May be hazardous in case of inhalation (lung corrosive). May be hazardous in case of ingestion.

Flammability

Health

Reactivity

Revisions

NFPA

1

The information herein is believed to be accurate and is offered in good faith for the user's consideration and investigation. No warranty either expressed or implied is made for the completeness or accuracy of the information whether originating from the above mentioned company or not. Users of this material should satisfy themselves by independent investigation of current scientific and medical knowledge that the material can be used safely.